



REIFEN 600 / 50 R 22.5
163 D, TL, CT
HEAVY DUTY, STEEL BELTED

Product-No.: 17415860

Technical Information:

Tyre size	600 / 50 R 22.5
TL / TT	TL
LI / SI	163 D
Tread	CT
Manufacturer	Nokian
Specification	HD/Steel Belted
Recom. Rim	AG20.00
Width [mm]	605
Outer diameter [mm]	1173
Static radius [mm]	528
Rolling circumference [mm]	3574
Payload in kg at kph (1)	4875 / 65
Inflation pressure [bar]	5,00
Weight [Kg]	141,1
Tyre content 75% [litre]	280
Stud height [mm]	22,0
Zulassung	nicht notwendig

Hints and features:

- The tyre's wide contact area enables good lateral stability when unloading and high flotation on soft surfaces
- The arrangement of the blocks with wide, angled spaces ensures good self-cleaning
- Its special wear-resistant rubber compound was developed for operations on challenging ground such as rocky surfaces, as well as for road use
- High-strength steel belt reinforcements combined with a cut- and crack-resistant rubber compound provide high puncture protection
- The special construction of several steel plies allows high inflation pressures and increases the stability of the tyre
- The asymmetrical arrangement of the blocks, which successively come into contact with the ground surface, reduces the noise generated when driving on the road