





Hints and features:

- The Alliance Agriflex 354 is a row crop tyre with IF technology for tractors, selfpropelled and towed field sprayers
- As an IF tyre, it has 20% more load capacity at the same inflation pressure or the same load capacity at 20% lower inflation pressure compared with a standard tyre
- This leads to optimal crop and soil protection
- The tyre provides high traction and excellent self-cleaning properties thanks to the stronger and optimally shaped lugs
- Its large contact area and steel belt construction also ensure traction and good ground pressure distribution
- The tyre is characterised by durability, reduced fuel costs and ride comfort

REIFEN IF 380 / 90 R 54 171 D, TL, AGRIFLEX 354 STEEL BELTED, ECE106

Product-No.: 15226724

Technical Information:

Tyre size	IF 380 / 90 R 54
TL/TT	TL
LI / SI	171 D
Tread	Agriflex 354
Manufacturer	Alliance
Specification	Steel Belted
Recom. Rim	13
Permissible rim	12
Width [mm]	380
Outer diameter [mm]	2056
Static radius [mm]	959
Rolling circumference [mm]	6231
Payload in kg at kph (1)	6150 / 65
Inflation pressure [bar]	4,40
Weight [Kg]	169,69
Tyre content 75% [litre]	325,5
Stud height [mm]	47,0
Number of studs	36x2
Zulassung	ECE 106
Tyre technology	IF
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.