



REIFEN 800 / 45 R 26.5  
184 A8 / 174 D, TL, FL 630 ULTRA  
ECE106

**Product-No.: 15715231**

#### Technical Information:

Tyre size	800 / 45 R 26.5
TL / TT	TL
LI / SI	184 A8 / 174 D
Tread	FL 630 Ultra
Manufacturer	BKT
Recom. Rim	AG28.00
Permissible rim	AG24.00
Width [mm]	828
Outer diameter [mm]	1393
Static radius [mm]	618
Rolling circumference [mm]	4238
Payload in kg at kph (1)	9000 / 40
Payload in kg at kph (2)	6700 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	187,3
Stud height [mm]	31,5
Zulassung	ECE 106

#### Hints and features:

- The BKT FL630 Ultra is a flotation tyre for use in the field and on the road
- It is mostly suitable for agricultural trailers, balers, heavy seeders and manure spreaders
- The robust tread pattern provides excellent traction even when cornering and manoeuvring
- The tyre guarantees good grip on all kinds of surfaces and has very good self-cleaning properties
- Its large contact area ensures very low soil compaction and optimum soil protection
- When driving on the road, the tyre is characterised by high ride comfort and low noise emission