



## Hints and features:

- Super-volume tyre for harvesters, self-propelled nutrient spreaders and high-performance tractors
- 45° lug angle for high traction with good self-cleaning properties
- Nylon casing with reinforced steel belt
- In conjunction with stubble guard rubber compound, optimum protection against punctures caused by e.g. corn stubble

REIFEN 680 / 85 R 32  
178 A8, TL, MULTISTAR 376  
ECE106

**Product-No.: 15226762**

## Technical Information:

Tyre size	680 / 85 R 32
TL / TT	TL
LI / SI	178 A8
Tread	Multistar 376
Manufacturer	Alliance
Recom. Rim	21
Width [mm]	660
Outer diameter [mm]	1960
Static radius [mm]	882
Rolling circumference [mm]	5823
Payload in kg at kph (1)	7500 / 40
Inflation pressure [bar]	3,20
Weight [Kg]	279,82
Tyre content 75% [litre]	835
Stud height [mm]	50,0
Number of studs	21x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.