



## Hints and features:

- The Ridemax IT 697 (M+S) is a municipal tyre suitable for various applications
- It is particularly suitable for state-of-theart contractors in winter operations
- The tyre offers excellent grip in the field on snow and ice, even without snow chains
- Thanks to its special tread pattern with sipes and its rubber compound, the tyre ensures full stability, comfort and safety in difficult, wintry road conditions
- The strong casing ensures durability and a long service life

REIFEN 540 / 65 R 28 160 A8 / 155 D, TL, RIDEMAX IT 697, M+S ECE106

Product-No.: 15775150

## **Technical Information:**

Tyre size	540 / 65 R 28
TL / TT	TL
LI/SI	160 A8 / 155 D
Tread	Ridemax IT 697
Manufacturer	BKT
Specification	M+S
Recom. Rim	W16L
Permissible rim	W18
Width [mm]	530
Outer diameter [mm]	1413
Static radius [mm]	642
Rolling circumference [mm]	4276
Payload in kg at kph (1)	4500 / 40
Payload in kg at kph (2)	3875 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	131,5
Stud height [mm]	26,5
Number of studs	30x2
Zulassung	ECE 106
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.