





Hints and features:

- The Nokian Hakka Truck Steer is an allseason tyre for local and long-distance transport
- The wide groove tread pattern offers durability through even wear and good ride comfort
- Sipe activators ensure good grip even on wet and slippery roads
- The special tread pattern ejects small stones and protects the tyre from damages

REIFEN 315 / 70 R 22.5 156 / 150 L, TL, HAKKA TRUCK STEER, 3PMSF NOKIAN (VA)

Product-No.: 17466365

Technical Information:

Tyre size	315 / 70 R 22.5
TL / TT	TL
LI/SI	156 / 150 L (154 / 150 M)
Tread	Hakka Truck Steer
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.25
Width [mm]	312
Outer diameter [mm]	1021
Static radius [mm]	471
Rolling circumference [mm]	3103
Payload in kg at kph (1)	4000 / 120
Payload in kg at kph (2)	3750 / 130
Loadcapacity Twin Truck	3350 / 120 (3350 / 130)
Inflation pressure [bar]	9,00
Weight [Kg]	64
Rolling resistance	С
Wet grip	В
Rolling Noise DB	70
Rolling Noise Level	Α
Stud height [mm]	14,0
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
LI 4	150

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.