



REIFEN 315 / 70 R 22.5  
154 / 150 L (152/148 M), TL, E-TRUCK DRIVE,  
3PMSF  
NOKIAN (HA)

**Product-No.: 17466515**

#### Technical Information:

Tyre size	315 / 70 R 22.5
TL / TT	TL
LI / SI	154 / 150 L (152 / 148 M)
Tread	E-Truck Drive
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Width [mm]	314
Outer diameter [mm]	1027
Static radius [mm]	474
Rolling circumference [mm]	3122
Payload in kg at kph (1)	3750 / 120
Payload in kg at kph (2)	3550 / 130
Loadcapacity Twin Truck	3350 / 120 (3150 / 130)
Inflation pressure [bar]	9,00
Weight [Kg]	67
Rolling resistance	D
Wet grip	B
Rolling Noise DB	73
Rolling Noise Level	A
Stud height [mm]	17,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF
LI 4	148

#### Hints and features:

- The Nokian E-Truck Drive is an all-season tyre for truck drive axles used in regional and long-distance transport
- Its tread pattern provides good grip, even in different road and weather conditions
- Its block pattern guarantees good traction
- The tread pattern wears evenly and ensures a long service life for the tyre
- Due to the low rolling resistance, the tyre provides low fuel consumption and good ride comfort