

**Kleber**



■ ■ ■ Bohnenkamp

REIFEN 230 / 95 R 44  
137 A8 / 134 D, TL, CROPKER  
(9.5 R 44)

**Product-No.: 12426800**

#### Technical Information:

Tyre size	230 / 95 R 44
TL / TT	TL
LI / SI	137 A8 / 134 D
Tread	Cropker
Manufacturer	Kleber
Recom. Rim	7
Permissible rim	8
Width [mm]	225
Outer diameter [mm]	1556
Static radius [mm]	738
Rolling circumference [mm]	4682
Payload in kg at kph (1)	2300 / 40
Payload in kg at kph (2)	2120 / 65
Inflation pressure [bar]	4,00
Weight [Kg]	55
Tyre content 75% [litre]	102
Stud height [mm]	31,0
Number of studs	31x2
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- The Kleber Cropker is a premium crop tyre for tractors in the 80-200 hp performance range
- Compared with its predecessor, the Kleber Super 3, the Cropker offers a higher load capacity and the double identifier D/A8
- It can be used as a FRT (Free Rolling Tyre) on towed vehicles with a load surcharge of up to 20% at 40 km/h
- Thanks to the special root-friendly lug shoulders, plants in row crops are optimally protected
- Its tread pattern reinforced in the centre of the tread provides improved driving and steering precision and longer mileage
- Due to the shape of the lugs and the spaces between them, the tyre offers very good self-cleaning properties