Bohnenkamp Moving Professionals



Hints and features:

- Implement tyre for trailers and other agricultural machines such as spreaders, balers, ploughs, seeders, etc.
- Tread pattern design and rounded shoulder area ensure soil protection in fields and low rolling resistance on the road

REIFEN 400 / 60 - 15.5 14 PR, 145 A8, TL, SG-316, AW ECE106

Product-No.: 19111130

Technical Information:

Tyre size	400 / 60 - 15.5
TL/TT	TL
LI / SI	145 A8
PR	14
Tread	SG-316
Manufacturer	Deli
Recom. Rim	AG13.00, AG13
Width [mm]	396
Outer diameter [mm]	870
Static radius [mm]	370
Rolling circumference [mm]	2578
Payload in kg at kph (1)	2900 / 40
Inflation pressure [bar]	3,60
Weight [Kg]	28,24
Stud height [mm]	10,4
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.