



Hints and features:

- The Windpower W847 IND-4 has a specially-shaped tyre bead
- Its particularly low-wear and low-heatgenerating rubber compound ensures a long service life
- The robust sidewalls provide very good stability
- The tyre is best suited for use in ports on e.g. forklifts and reach stackers
- Attention: only approved for mounting on multi-part rim

REIFEN 14.00 R 24 193 A5, TL, W 847 IND-4\*\*\* (385/95R24)

Product-No.: 10485022

## **Technical Information:**

Tyre size	14.00 R 24
TL/TT	TL
LI/SI	193 A5
Tread	W 847
Manufacturer	Windpower
Specification	IND4, ***
Recom. Rim	10.00/1.5
Width [mm]	380
Outer diameter [mm]	1420
Payload in kg at kph (1)	11500 / 25
Inflation pressure [bar]	10,00
Weight [Kg]	214,3
Stud height [mm]	47,5
Zulassung	nicht notwendig
Star Rating	***
Direction bound	Yes
TRA Code	IND4

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.