



REIFEN 420 / 65 R 24  
126 A8 / 126 B, TL, AGRISTAR 365  
ECE106

**Product-No.: 15226728**

#### Technical Information:

Tyre size	420 / 65 R 24
TL / TT	TL
LI / SI	126 A8 / 126 B
Tread	Agristar 365
Manufacturer	Alliance
Recom. Rim	13
Width [mm]	418
Outer diameter [mm]	1156
Static radius [mm]	580
Rolling circumference [mm]	3415
Payload in kg at kph (1)	1700 / 40
Payload in kg at kph (2)	1700 / 50
Inflation pressure [bar]	1,60
Weight [Kg]	63,2
Tyre content 75% [litre]	153
Stud height [mm]	37,0
Number of studs	20x2
Zulassung	ECE 106
Direction bound	Yes

#### Hints and features:

- Agricultural radial wide tyre of the 65 series (70 series with 710 width) for powerful tractors up to approx. 250 hp
- Very gentle tillage due to high air volume and large contact area
- Lug shape and arrangement allows optimum traction power distribution
- With 65 km/h approval, suitable for frequent road use

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.