Bohnenkamp Moving Professionals

TRELLEBORG



Hints and features:

- Modern agricultural tyre, approved up to 65 km/h
- Maximum performance in the field due to extra-large contact area
- High level of comfort
- Long service life

REIFEN 440 / 65 R 24 128 D, TL, TM 800 **DA**

Product-No.: 13626173

Technical Information:

| Tyre size | 440 / 65 R 24 |
|----------------------------|-----------------|
| TL / TT | TL |
| LI / SI | 128 D |
| Tread | TM800 |
| Manufacturer | Trelleborg |
| Recom. Rim | 14 |
| Permissible rim | 13, 15 |
| Width [mm] | 441 |
| Outer diameter [mm] | 1182 |
| Static radius [mm] | 537 |
| Rolling circumference [mm] | 3.545 |
| Payload in kg at kph (1) | 1800 / 65 |
| Inflation pressure [bar] | 1,60 |
| Weight [Kg] | 73 |
| Tyre content 75% [litre] | 202 |
| Stud width [mm] | 40 |
| Stud height [mm] | 45,0 |
| Number of studs | 20x2 |
| Zulassung | nicht notwendig |
| | |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.