Bohnenkamp Moving Professionals



Hints and features:

LKW-ALU-FELGE 8.25 X 22.5 ILV, POLISH+ACCU-SHIELD 10/281/335, Ø32, M20/M22, MZ, ET +148 HMA 170 3650 KG - 130 KM/H, 40014XPC

Product-No.: 30964045

Technical Information:

Manufacturer	Accuride
Material	Aluminium
Bolt hole execution	M20/M22
Rim size	8,25 x 22.5
Ein- / Mehrteilig	einteilig
Hump	kein Hump
Hole count	10
Hub Bore	281
Bolt circle	335
Felgenzentrierung (Felgen)	MZ
ET	+148
Colour	Silber
Load capacity 1 [kg]	3.650
Speed 1 [km/h]	130
Loadcapacity 2 [kg]	3.285
Weight [Kg]	23,4
Ventilsitz	ILV
perm. drive type	Angetriebene & gezogene Achse

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.