



Hints and features:

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders
- Strong radial casing ensures high load capacities and maximum stability in use
- Optimised rubber compound and angled centre lugs for hard surfaces
- High wear resistance and consequently a long service life
- Ideal for biogas plants

REIFEN 400 / 70 R 20

149 A8 / 149 B, TL, AGRO INDUSTRIAL 580
ECE106

Product-No.: 15285281

Technical Information:

Tyre size	400 / 70 R 20
TL / TT	TL
LI / SI	149 A8 / 149 B
Tread	Agro Industrial 580
Manufacturer	Alliance
Recom. Rim	13
Permissible rim	12, 14
Width [mm]	410
Outer diameter [mm]	1072
Static radius [mm]	485
Rolling circumference [mm]	3239
Payload in kg at kph (1)	3250 / 40
Payload in kg at kph (2)	3250 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	76,18
Stud height [mm]	32,0
Number of studs	18x2
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.