



REIFEN VF 480 / 80 R 46
177 D, TL, AGRIMAX SPARGO
ECE106

Product-No.: 15726467

Technical Information:

Tyre size	VF 480 / 80 R 46
TL / TT	TL
LI / SI	177 D
Tread	Agrimax Spargo
Manufacturer	BKT
Recom. Rim	16
Permissible rim	15
Width [mm]	479
Outer diameter [mm]	1936
Static radius [mm]	889
Rolling circumference [mm]	5861
Payload in kg at kph (1)	7300 / 65
Inflation pressure [bar]	3,60
Weight [Kg]	221
Tyre content 75% [litre]	439,5
Stud height [mm]	43,5
Number of studs	30x2
Zulassung	ECE 106
Tyre technology	VF
Direction bound	Yes

Hints and features:

- Row crop tyre with VF technology for self-propelled and towed field sprayers and tractors
- Up to 40% higher load capacity at constant inflation pressure or up to 40% lower inflation pressure with the same payload compared with standard tyres
- Excellent plant and soil protection allows yield increases
- Excellent ride comfort and high machine stability

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.