



Hints and features:

- Increased payload, especially for use with caravans and trailers
- Reinforced sidewall design
- Special tread pattern design for stable driving behaviour

RAD 185 R 14 C BOKA TRAILER LINE FT 02, M+S
104 / 102 N, TL, 5/66.6/112, Ø15MM, C60, ET +30
ALU 5.5 J X 14 H2, SILBER

Product-No.: 59600361

Technical Information:

Wheel size	185 R 14 C
LI / PR	104 / 102 N, 8 PR
Tread	FT 02
Manufacturer	Boka Trailer Line
Rim	5.5 J x 14 H2
Connection	5/66.6/112
Rim centering	BZ
ET	+30
Width [mm]	188
Outer diameter [mm]	650
Rolling circumference [mm]	2048
Inflation pressure [bar]	4,50
Loadcapacity Tyre	900 / 140
Loadcapacity Rim	950 / 140
Loadcapacity compl. Wheel	900 / 140
Loadcapacity Twin Truck	850 / 140
Tread depth [mm]	6,2
Rolling resistance	C
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Rim meterial	Aluminium
Weight [Kg]	17,33

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.