



Hints and features:

- Reinforced sidewall design
- The special flat tread design for trailer & caravan use ensures optimum running smoothness and driving stability
- Low abrasion due to a special rubber compound
- Increased payload

RAD 195 / 70 R 14 BOKA TRAILER LINE FT 01, M+S

96 N, TL, 5/66.6/112, Ø15MM, C60 (KEGEL), ET +30

ALU 5.5 X 14, SILBER

Product-No.: 59758078

Technical Information:

Wheel size	195 / 70 R 14
LI / PR	96 N
Tread	FT 01
Manufacturer	Boka Trailer Line
Rim	5.5 J x 14 H2
Connection	5/66.6/112
Rim centering	BZ
ET	+30
Width [mm]	201
Outer diameter [mm]	630
Rolling circumference [mm]	1972
Inflation pressure [bar]	3,40
Loadcapacity Tyre	710 / 140
Loadcapacity Rim	950 / 140
Loadcapacity compl. Wheel	710 / 140
Tread depth [mm]	6,2
Rolling resistance	D
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Rim meterial	Aluminium
Weight [Kg]	15,48

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.