



REIFEN 315 / 80 R 22.5
156 / 150 K, TL, R-TRUCK DRIVE, 3PMSF
NOKIAN (HA)

Product-No.: 17466404

Technical Information:

Tyre size	315 / 80 R 22.5
TL / TT	TL
LI / SI	156 / 150 K
Tread	R-Truck Drive
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width [mm]	312
Outer diameter [mm]	1076
Static radius [mm]	500
Rolling circumference [mm]	3271
Payload in kg at kph (1)	4000 / 110
Loadcapacity Twin Truck	3350 / 110
Inflation pressure [bar]	8,25
Weight [Kg]	69
Rolling resistance	D
Wet grip	C
Rolling Noise DB	75
Rolling Noise Level	B
Stud height [mm]	21,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

Hints and features:

- The Nokian R-Truck Drive is a truck tyre for the drive axle for year-round use in various conditions, on construction sites, forest paths and asphalted roads
- The non-directional, open tread pattern has good self-cleaning properties and provides excellent grip in changing driving conditions
- Large tread blocks reduce material separation and the formation of cracks
- Stone ejectors in the main grooves prevent the penetration of small stones
- The low heat development during road use enables even wear and a long service life for the tyre
- When on the road, R-Truck tyres are particularly quiet and have a low rolling resistance
- All R-Truck tyres are characterised by very good puncture protection, even in the toughest conditions

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.