Bohnenkamp Moving Professionals



Hints and features:

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre
- The tyre can be fitted with spikes and driven with tyre chains
- It provides high loading capacities at speeds up to 65 km/h

REIFEN 540 / 70 R 30 159 D, TL, TRACTOR KING STEEL BELTED

Product-No.: 17426640

Technical Information:

Tyre size	540 / 70 R 30
TL / TT	TL
LI / SI	159 D
Tread	Tractor King
Manufacturer	Nokian
Specification	R1, Steel Belted
Recom. Rim	DW16L
Permissible rim	TW16L, TW18L
Width [mm]	540
Outer diameter [mm]	1518
Static radius [mm]	693
Rolling circumference [mm]	4539
Payload in kg at kph (1)	4375 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	195,65
Tyre content 75% [litre]	360
Stud height [mm]	50,0
Zulassung	nicht notwendig
TRA Code	R1

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.