



## Hints and features:

- The Nokian E-Truck is an all-season tyre for truck steer axles or buses used in regional and long-distance transport
- Thanks to its spiral-shaped sipes, the tyre ensures very good handling on wet roads
- Its special zigzag-shaped grooves eject small stones and prevent damage
- The tread pattern wears evenly and ensures a long service life for the tyre

REIFEN 295 / 80 R 22.5 152 / 148 M, TL, E-TRUCK STEER, 3PMSF NOKIAN (VA)

Product-No.: 17466500

## **Technical Information:**

Tyre size	295 / 80 R 22.5
TL/TT	TL
LI/SI	152 / 148 M
Tread	E-Truck Steer
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	8.25
Width [mm]	298
Outer diameter [mm]	1044
Static radius [mm]	487
Rolling circumference [mm]	3173
Payload in kg at kph (1)	3550 / 130
Payload in kg at kph (2)	3150
Loadcapacity Twin Truck	3150 / 130
Inflation pressure [bar]	8,50
Weight [Kg]	63
Rolling resistance	С
Wet grip	В
Rolling Noise DB	70
Rolling Noise Level	A
Stud height [mm]	13,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.