



REIFEN 295 / 80 R 22.5
152 / 148 M, TL, E-TRUCK DRIVE, 3PMSF
NOKIAN (HA)

Product-No.: 17466505

Technical Information:

Tyre size	295 / 80 R 22.5
TL / TT	TL
LI / SI	152 / 148 M
Tread	E-Truck Drive
Manufacturer	Nokian
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	8.25
Width [mm]	298
Outer diameter [mm]	1044
Static radius [mm]	491
Rolling circumference [mm]	3204
Payload in kg at kph (1)	3550 / 130
Payload in kg at kph (2)	3150
Inflation pressure [bar]	8,50
Weight [Kg]	63
Rolling resistance	D
Wet grip	C
Rolling Noise DB	75
Rolling Noise Level	B
Stud height [mm]	17,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

Hints and features:

- The Nokian E-Truck Drive is an all-season tyre for truck drive axles used in regional and long-distance transport
- Its tread pattern provides good grip, even in different road and weather conditions
- Its block pattern guarantees good traction
- The tread pattern wears evenly and ensures a long service life for the tyre
- Due to the low rolling resistance, the tyre provides low fuel consumption and good ride comfort