



Hints and features:

- The Michelin Axiobib 2 is suitable for tractors from 160 hp up to 550 hp
- The VF tyre with its Ultraflex technology enables increased load capacity by up to 40%
- Furthermore, the tyre is characterised by its low inflation pressure and excellent traction in the field

REIFEN VF 650 / 85 R 42
183 D / 180 E, TL, AXIOBIB 2

Product-No.: 13326653

Technical Information:

Tyre size	VF 650 / 85 R 42
TL / TT	TL
LI / SI	183 D / 180 E
Tread	AxioBib 2
Manufacturer	Michelin
Recom. Rim	DW23B(A)
Permissible rim	DW21B(A)
Width [mm]	670
Outer diameter [mm]	2164
Static radius [mm]	948
Rolling circumference [mm]	6393
Payload in kg at kph (1)	8750 / 65
Payload in kg at kph (2)	8000 / 70
Inflation pressure [bar]	2,00
Weight [Kg]	390
Tyre content 75% [litre]	913,5
Stud height [mm]	61,0
Number of studs	21x2
Zulassung	nicht notwendig
Tyre technology	VF
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.