



## REIFEN 26.5 R 25 202 A2 / 193 B, TL, EARTHMAX SR 31 L3\* / E3\*\*, CUT RESISTANT

**Product-No.: 15785531**

### Technical Information:

Tyre size	26.5 R 25
TL / TT	TL
LI / SI	202 A2 / 193 B
Tread	Earthmax SR 31
Manufacturer	BKT
Specification	E3/L3, **/*, C.R.
Recom. Rim	22.00/3.0
Width [mm]	689
Outer diameter [mm]	1742
Static radius [mm]	766
Rolling circumference [mm]	5200
Payload in kg at kph (1)	15000 / 10
Payload in kg at kph (2)	11500 / 50
Inflation pressure [bar]	5,25
Weight [Kg]	464,51
Tyre content 75% [litre]	637,5
Stud height [mm]	38,0
Zulassung	nicht notwendig
Star Rating	**, *
TRA Code	E3, L3

### Hints and features:

- The Earthmax SR 31 is an all-steel radial tyre for use on wheel loaders, bulldozers and articulated dump trucks
- Its construction with multiple steel band layers provides extraordinary strength and stability
- Its non-directional tread pattern ensures first-class traction and manoeuvrability, even on muddy ground, and also offers a high level of ride comfort
- Thanks to its cut- and heat-resistant tread compound, the tyre has a long service life
- The reduced rolling resistance results in significant fuel savings