Bohnenkamp Moving Professionals

CARLISLE



Hints and features:

- Tyre for professional use on lawns, gardens and golf courses
- Durable rubber compound in conjunction with deep tread blocks
- Tread pattern optimised for stability and traction

REIFEN 280 / 55 - 15 8 PR, 102 B, TL, MULTI TRAC C/S (27X10.50-15), ECE106

Product-No.: 12598089

Technical Information:

	280 / 55 - 15
Tyre size	
TL/TT	TL
LI / SI	102 B
PR	8
Tread	Multi Trac C/S
Manufacturer	Carlisle
Recom. Rim	8.50
Permissible rim	8LB
Width [mm]	285
Outer diameter [mm]	693
Static radius [mm]	314
Rolling circumference [mm]	2095
Payload in kg at kph (1)	850 / 50
Inflation pressure [bar]	4,10
Weight [Kg]	14,6
Stud height [mm]	8,9
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.