





Hints and features:

- Tyre for professional use on lawns, gardens and golf courses
- Durable rubber compound in conjunction with deep tread blocks
- Tread pattern optimised for stability and traction

REIFEN 44 X 18.00 - 20 4 PR, 123 B, TL, MULTI TRAC R-3 (450/65-20), ECE106

Product-No.: 12598095

Technical Information:

Tyre size	44 x 18.00 - 20
TL / TT	TL
LI/SI	123 B
PR	4
Tread	Multi Trac R-3
Manufacturer	Carlisle
Specification	R3
Recom. Rim	14.00
Permissible rim	W14L, W14LH
Width [mm]	457
Outer diameter [mm]	1156
Static radius [mm]	526
Rolling circumference [mm]	3505
Payload in kg at kph (1)	1550 / 50
Inflation pressure [bar]	1,40
Weight [Kg]	61,7
Stud height [mm]	19,8
Zulassung	ECE 106
TRA Code	R3
Specification Recom. Rim Permissible rim Width [mm] Outer diameter [mm] Static radius [mm] Rolling circumference [mm] Payload in kg at kph (1) Inflation pressure [bar] Weight [Kg] Stud height [mm] Zulassung	Carlisle R3 14.00 W14L, W14LH 457 1156 526 3505 1550 / 50 1,40 61,7 19,8 ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.