Bohnenkamp Moving Professionals

KENDA



Hints and features:

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and midrange tandem trailers
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof

REIFEN 145 / 80 R 10 74 N, TL, KR209 KARGOTRAIL 3G, M+S

Product-No.: 19266064

Technical Information:

Tyre size	145 / 80 R 10
TL / TT	TL
LI / SI	74 N
Tread	KR209 KargoTrail 3G
Manufacturer	Kenda
Specification	M+S
Recom. Rim	3.5B
Permissible rim	3.50B, 4.00B, 4.50B
Width [mm]	144
Outer diameter [mm]	486
Static radius [mm]	217
Rolling circumference [mm]	1479
Payload in kg at kph (1)	375 / 140
Inflation pressure [bar]	3,40
Weight [Kg]	4,25
Stud height [mm]	5,0
Zulassung	ECE 30
M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.