

**KENDA**



REIFEN 135 / 80 R 13  
70 N, TL, KR209 KARGOTRAIL 3G, M+S

**Product-No.: 19266113**

#### Technical Information:

Tyre size	135 / 80 R 13
TL / TT	TL
LI / SI	70 N
Tread	KR209 KargoTrail 3G
Manufacturer	Kenda
Specification	M+S
Recom. Rim	3.50J
Permissible rim	3.50 B, 4J, 4.00 B, 4.50J, 4.50 B
Width [mm]	133
Outer diameter [mm]	546
Static radius [mm]	249
Rolling circumference [mm]	1665
Payload in kg at kph (1)	335 / 140
Inflation pressure [bar]	3,00
Weight [Kg]	4,5
Rolling resistance	C
Wet grip	D
Rolling Noise DB	69
Rolling Noise Level	B
Stud height [mm]	5,0
Zulassung	ECE 30, ECE 117
M+S	M+S

#### Hints and features:

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and mid-range tandem trailers
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof