

KENDA



REIFEN 165 / 70 R 13
79 N, TL, KR209 KARGOTRAIL 3G, M+S

Product-No.: 19266118

Technical Information:

Tyre size	165 / 70 R 13
TL / TT	TL
LI / SI	79 N
Tread	KR209 KargoTrail 3G
Manufacturer	Kenda
Specification	M+S
Recom. Rim	5J
Permissible rim	4J, 4.00B, 4.50J, 4.50B, 5.00B, 5.50J
Width [mm]	172
Outer diameter [mm]	564
Static radius [mm]	256
Rolling circumference [mm]	1720
Payload in kg at kph (1)	437 / 140
Inflation pressure [bar]	3,00
Weight [Kg]	5,5
Rolling resistance	C
Wet grip	D
Rolling Noise DB	69
Rolling Noise Level	B
Stud height [mm]	5,0
Zulassung	ECE 30, ECE 117
M+S	M+S

Hints and features:

- The Kenda KR209 KargoTrail 3G is a tyre for single axle car trailers and mid-range tandem trailers
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.