

KENDA



REIFEN 165 R 13 C
96 / 94 N, TL, KR101 MASTERTRAIL 3G, M+S

Product-No.: 19266121

Technical Information:

Tyre size	165 R 13 C
TL / TT	TL
LI / SI	96 / 94 N
Tread	KR101 MasterTrail 3G
Manufacturer	Kenda
Specification	M+S
Recom. Rim	4.50J
Permissible rim	4J, 5J
Width [mm]	167
Outer diameter [mm]	596
Static radius [mm]	269
Rolling circumference [mm]	1806
Payload in kg at kph (1)	710 / 140
Loadcapacity Twin Truck	670 / 140
Inflation pressure [bar]	4,50
Weight [Kg]	7,5
Rolling resistance	B
Wet grip	C
Rolling Noise DB	72
Rolling Noise Level	B
Stud height [mm]	5,8
Zulassung	ECE 54, ECE 117
M+S	M+S

Hints and features:

- The Kenda KR101 MasterTrail 3G is a tyre for single axle car trailers, tandem, tridem and other heavy trailers
- The strong casing enables very high loading capacities
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof