





Hints and features:

- The Kenda KR101 MasterTrail 3G is a tyre for single axle car trailers, tandem, tridem and other heavy trailers
- The strong casing enables very high loading capacities
- Due to its tread pattern, the tyre provides low rolling resistance, good wet grip and low noise
- The high number of sipes ensures good dispersion of water, slush and snow for excellent driving performance all year round
- The reinforced inner liner construction keeps the tyre particularly airtight and puncture-proof

REIFEN 195 / 50 R 13 C 104 / 102 N, TL, KR101 MASTERTRAIL 3G, M+S

Product-No.: 19266122

Technical Information:

TL / TT LI / SI Tread KR101 MasterTrail 3G Manufacturer Kenda Specification M+S Recom. Rim 6J Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] Static radius [mm] Rolling circumference [mm] Payload in kg at kph (1) 900 / 140	Tyre size	195 / 50 R 13 C
Tread KR101 MasterTrail 3G Manufacturer Kenda Specification M+S Recom. Rim 6J Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	TL / TT	TL
Manufacturer Kenda Specification M+S Recom. Rim 6J Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	LI/SI	104 / 102 N
Specification M+S Recom. Rim 6J Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Tread	KR101 MasterTrail 3G
Recom. Rim 6J Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Manufacturer	Kenda
Permissible rim 5.50J, 6.50J Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Specification	M+S
Width [mm] 195 Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Recom. Rim	6J
Outer diameter [mm] 526 Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Permissible rim	5.50J, 6.50J
Static radius [mm] 240 Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Width [mm]	195
Rolling circumference [mm] 1603 Payload in kg at kph (1) 900 / 140	Outer diameter [mm]	526
Payload in kg at kph (1) 900 / 140	Static radius [mm]	240
	Rolling circumference [mm]	1603
	Payload in kg at kph (1)	900 / 140
Loadcapacity Twin Truck 850 / 140	Loadcapacity Twin Truck	850 / 140
Inflation pressure [bar] 6,50	Inflation pressure [bar]	6,50
Weight [Kg] 7,3	Weight [Kg]	7,3
Rolling resistance B	Rolling resistance	В
Wet grip C	Wet grip	С
Rolling Noise DB 72	Rolling Noise DB	72
Rolling Noise Level B	Rolling Noise Level	В
Stud height [mm] 5,8	Stud height [mm]	5,8
Zulassung ECE 54, ECE 117	Zulassung	ECE 54, ECE 117
M+S M+S	M+S	M+S

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.