



#### Hints and features:

- The Ling Long KTS300 is a truck steering axle tyre for use in regional transport
- Its optimised shoulder construction provides improved protection against damages to the tyre shoulder
- Stone deflectors protect the tread pattern from damages by preventing small stones from penetrating the tread
- The tyre is very wear resistant and guarantees good grip and stability over its entire service life

REIFEN 315 / 60 R 22.5  
16 PR, 152 / 148 L, TL, KTS300, 3PMSF  
LINGLONG (VA / TR)

**Product-No.: 11366130**

#### Technical Information:

Tyre size	315 / 60 R 22.5
TL / TT	TL
LI / SI	152 / 148 L
PR	16
Tread	KTS300
Manufacturer	Linglong
Specification	3PMSF
Recom. Rim	9.75
Permissible rim	9.00
Width [mm]	313
Outer diameter [mm]	950
Static radius [mm]	445
Rolling circumference [mm]	2878
Payload in kg at kph (1)	3550 / 120
Loadcapacity Twin Truck	3150 / 120
Inflation pressure [bar]	9,00
Weight [Kg]	56,26
Rolling resistance	D
Wet grip	C
Rolling Noise DB	73
Rolling Noise Level	B
Stud height [mm]	14,5
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF