





## Hints and features:

- The Kenda KR500 is an all-season trailer tyre
- It provides safe and comfortable driving in wintry conditions
- The extra wide grooves help to disperse water and snow, ensuring safety in wintry road conditions

REIFEN 155 R 13 C 91 / 89 N, TL, KR500 WINTER TRAILER, 3PMSF

Product-No.: 19266109

## **Technical Information:**

Tyre size	155 R 13 C
TL / TT	TL
LI/SI	91 / 89 N
Tread	KR500 Winter Trailer
Manufacturer	Kenda
Specification	3PMSF, Spikefähig
Recom. Rim	4.00B
Permissible rim	4J, 4.50B, 4.50J, 5.0B, 5J
Width [mm]	149
Outer diameter [mm]	576
Payload in kg at kph (1)	615 / 140
Loadcapacity Twin Truck	580 / 140
Inflation pressure [bar]	4,50
Weight [Kg]	6,77
Rolling resistance	E
Wet grip	В
Rolling Noise DB	72
Rolling Noise Level	В
Stud height [mm]	8,7
Zulassung	ECE 117, ECE 54
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.