



REIFEN 620 / 75 R 30 169 D, TL, TRACTOR KING STEEL BELTED

Product-No.: 17426644

Technical Information:

Tyre size	620 / 75 R 30
TL / TT	TL
LI / SI	169 D
Tread	Tractor King
Manufacturer	Nokian
Specification	R1, Steel Belted
Recom. Rim	DW20B
Permissible rim	TW20B
Width [mm]	625
Outer diameter [mm]	1692
Static radius [mm]	770
Rolling circumference [mm]	5097
Payload in kg at kph (1)	5800 / 65
Inflation pressure [bar]	3,20
Weight [Kg]	275,96
Tyre content 75% [litre]	565
Stud height [mm]	52,0
Zulassung	nicht notwendig
Direction bound	Yes
TRA Code	R1

Hints and features:

- The Nokian Tractor King is a tractor tyre for heavy machines on rough terrain, in forestry and earthmoving applications and on building sites
- Due to the strong steel belted casing and the robust sidewall, the tyre is protected against damages and premature wear
- Its big contact area and the innovative tread pattern with a high number of traction edges guarantee good traction on any surface
- Stone ejectors prevent damage caused by the penetration of stones and thus ensure a long service life for the tyre
- The tyre can be fitted with spikes and driven with tyre chains
- It provides high loading capacities at speeds up to 65 km/h