

**VREDESTEIN**  
TYRES



#### Hints and features:

- The Vredestein Traxion Optimall is a new VF tyre for high-performance tractors
- Its extremely flexible casing design enables a reduction of the inflation pressure by up to 25 percent for low soil compaction
- The upper bead zone is reinforced for good stability even at low inflation pressure
- The strong lug end in the tread centre provides stability, low tread wear and good self-cleaning properties
- In on-road use, the tread with a high amount of rubber grants low wear and a long service lifespan
- The rounded tread contour enables good driving comfort
- Thanks to the NRO technology, the tyre can be mounted on a narrower rim as other VF tyres of the same dimension

REIFEN VF 650 / 65 R 34 NRO  
170 D, TL, TRAXION OPTIMALL  
ECE106

**Product-No.: 14827113**

#### Technical Information:

Tyre size	VF 650 / 65 R 34 NRO
TL / TT	TL
LI / SI	170 D
Tread	TRAXION OPTIMALL
Manufacturer	Vredestein
Recom. Rim	DW23B
Permissible rim	DW21B, DW20B
Width [mm]	655
Outer diameter [mm]	1715
Static radius [mm]	775
Rolling circumference [mm]	5100
Payload in kg at kph (1)	6000 / 65
Inflation pressure [bar]	2,00
Weight [Kg]	249,49
Tyre content 75% [litre]	508
Stud height [mm]	58,0
Zulassung	ECE 106
NRO	NRO
Tyre technology	VF
Direction bound	Yes