



#### Hints and features:

- Newly-developed flotation tyre with steel belt reinforcement
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use
- Directional block tread pattern for low rolling resistance and very good self-cleaning
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure
- Steel belt offers additional protection against punctures

RAD 710 / 50 R 26.5 ALLIANCE 882  
172 D, TL, 10/281/335, A3, ET -50  
24.00 X 26.5, RAL9006 SILBER

**Product-No.: 59911791**

#### Technical Information:

Wheel size	710 / 50 R 26.5
LI / PR	172 D
Tread	882
Manufacturer	Alliance
Rim	AG 24.00 x 26.5 TH2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
ET	-50
Width [mm]	727
Outer diameter [mm]	1383
Static radius [mm]	623
Rolling circumference [mm]	4219
Inflation pressure [bar]	4,00
Loadcapacity Tyre	6300 / 65
Loadcapacity Rim	10200 / 40
Loadcapacity compl. Wheel	6300 / 65
Number of studs	14x2
Tread depth [mm]	22,5
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	253,15