

## Firestone



### Hints and features:

- Suitable for industrial use and simple, multi-purpose application in agriculture
- Excellent side stability and safety
- Cut and puncture resistant
- Solid grip on hard surfaces

REIFEN 460 / 70 R 24  
159 A8 / 159 B, TL, R8000 UTILITY

**Product-No.: 10627381**

### Technical Information:

Tyre size	460 / 70 R 24
TL / TT	TL
LI / SI	159 A8 / 159 B
Tread	R8000 Utility
Manufacturer	Firestone
Recom. Rim	W15L
Permissible rim	W14L, DW14L, DW15L
Width [mm]	486
Outer diameter [mm]	1274
Static radius [mm]	573
Rolling circumference [mm]	3850
Payload in kg at kph (1)	4375 / 40
Payload in kg at kph (2)	4375 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	93,7
Stud height [mm]	31,0
Number of studs	27x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.