

**Mitas**



REIFEN 620 / 75 R 30  
169 A8 / 166 D, TL, SFT

**Product-No.: 10927923**

#### Technical Information:

Tyre size	620 / 75 R 30
TL / TT	TL
LI / SI	169 A8 / 166 D
Tread	SFT
Manufacturer	Mitas
Recom. Rim	DW20B
Permissible rim	DW18L, DW21B
Width [mm]	635
Outer diameter [mm]	1700
Static radius [mm]	740
Rolling circumference [mm]	4980
Payload in kg at kph (1)	5800 / 40
Payload in kg at kph (2)	5300 / 65
Inflation pressure [bar]	2,80
Weight [Kg]	207,8
Tyre content 75% [litre]	550
Stud height [mm]	54,0
Number of studs	19x2
Zulassung	nicht notwendig
Direction bound	Yes

#### Hints and features:

- The Mitas SFT was developed for high-performance machines above 180 hp
- Its big contact area provides excellent traction
- The flexible sidewalls enable high load capacities even at low inflation pressure

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.