

CARLISLE



REIFEN 250 / 40 - 10
2 PR, 70 A4, TL, SMOOTH
(18x10.50-10), ECE106

Product-No.: 12500603

Technical Information:

Tyre size	250 / 40 - 10
TL / TT	TL
LI / SI	70 A4
PR	2
Tread	Smooth
Manufacturer	Carlisle
Recom. Rim	8.00
Width [mm]	248
Outer diameter [mm]	460
Static radius [mm]	204
Rolling circumference [mm]	1362
Payload in kg at kph (1)	335 / 20
Inflation pressure [bar]	0,83
Weight [Kg]	5,6
Zulassung	ECE 106

Hints and features:

- The Carlisle Smooth is a tyre for transport vehicles, ride-on mowers, garden tractors and wheelbarrows
- The smooth tread pattern with rounded shoulders protects the soil and does not leave any traces on the ground
- Thanks to the special rubber compound, the tyre is very durable

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.