



Hints and features:

- Ideal for longer transport and grassland use
- Block tread for smooth handling on long road journeys and ground protection when driving on grassland
- Low rolling resistance for minimum fuel consumption
- The special tyre construction enables speeds up to 80 km/h
- High tread depth for a long service lifespan
- All-steel carcass with continuous steel insert plus 3 steel belt layers for maximum demands and workload

RAD 600 / 50 R 22.5 ALLIANCE 390
166 F, TL, 10/281/335, M22, Ø26MM, MZ, ET 0
20.00 X 22.5, RAL9006 SILBER, VS H, ALL
STEEL

Product-No.: 59913532

Technical Information:

Wheel size	600 / 50 R 22.5
LI / PR	166 F
Tread	390
Manufacturer	Alliance
Rim	AG 20.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	M22
Rim centering	MZ
Width [mm]	585
Outer diameter [mm]	1180
Static radius [mm]	539
Rolling circumference [mm]	3510
Inflation pressure [bar]	6,00
Loadcapacity Tyre	5300 / 80
Loadcapacity Rim	5100 / 100
Loadcapacity compl. Wheel	5300 / 80
Tread depth [mm]	25,0
Rim material	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	196,31