Bohnenkamp

Moving Professionals

nokian[®] TYRES



Hints and features:

- Multifunctional tyre for agricultural trailers and vehicles
- Approved for speeds up to 65 km/h
- Very high payload
- Excellent on-road and off-road ride comfort
- Self-cleaning tread pattern reduces traces of soil on the road
- Steel belted for high mileage and durability
- Low rolling resistance reduces fuel costs

RAD 560 / 60 R 22.5 NOKIAN COUNTRY KING 161 D, TL, 10/281/335, A3, ET 0 16.00 X 22.5

Product-No.: 59914404

Technical Information:

Wheel size	560 / 60 R 22.5
LI / PR	161 D
Tread	Country King
Manufacturer	Nokian
Rim	AG 16.00 x 22.5 H2
Connection	10/281/335
Bolt hole execution	A3
Rim centering	BZ
Width [mm]	564
Outer diameter [mm]	1244
Static radius [mm]	557
Rolling circumference [mm]	3764
Inflation pressure [bar]	4,00
Loadcapacity Tyre	4625 / 65
Loadcapacity Rim	7600 / 40
Tyre content 75% [litre]	390
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	150

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.