

WINDPOWER
Get Your Job Done



Hints and features:

- Construction site tyre of the newest generation for drive axles
- Strong hexagonal tread for excellent traction on tough terrain
- Reinforced casing to protect against cuts and tread separation
- Very good self-cleaning properties

RAD 385 / 65 R 22.5 WINDPOWER WGC 28 3PMSF
20 PR, 160 K / 158 L, 10/281/335, B33 BMZ, ET 0
11.75 X 22.5, RAL9006 SILBER, ALV

Product-No.: 59967879

Technical Information:

Wheel size	385 / 65 R 22.5
LI / PR	164 K (158 L), 20 PR
Tread	WGC 28
Manufacturer	Windpower
Rim	11.75 x 22.5
Connection	10/281/335
Bolt hole execution	B33
Rim centering	BMZ
Width [mm]	387
Outer diameter [mm]	1070
Static radius [mm]	499
Rolling circumference [mm]	3264
Inflation pressure [bar]	9,00
Loadcapacity Tyre	5000 / 110
Loadcapacity Rim	5000 / 130
Loadcapacity compl. Wheel	4500 / 110
Tread depth [mm]	16,8
Rolling resistance	C
Wet grip	C
Rolling Noise DB	74
Rolling Noise Level	B
Rim meterial	Stahl
RAL / Color	RAL9006 / Silber
Weight [Kg]	114,43

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.