



REIFEN 360 / 70 R 24
122 D, TL, AGRIMAX RT 765
ECE106

Product-No.: 15726611

Technical Information:

Tyre size	360 / 70 R 24
TL / TT	TL
LI / SI	122 D
Tread	Agrimax RT 765
Manufacturer	BKT
Recom. Rim	W11
Permissible rim	W10, W12
Width [mm]	357
Outer diameter [mm]	1152
Static radius [mm]	519
Rolling circumference [mm]	3395
Payload in kg at kph (1)	1500 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	60,75
Tyre content 75% [litre]	123,75
Stud width [mm]	33
Stud height [mm]	41,0
Number of studs	19x2
Zulassung	ECE 106
Direction bound	Yes

Hints and features:

- Wide-base tyre of the 70 series for tractors in the low- to medium-power range.
- Principal areas of use: arable farming and grassland
- Low soil compaction and good self-cleaning properties
- Optimised rubber compound: 25 % less wear, 30 % improved resistance to cuts and shedding, 20% more traction

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.