

Mitas



Hints and features:

- The Mitas AC 85 Row Crop is a row crop tyre
- Its optimum lug height ensures very good traction and tracking as well as good self-cleaning properties
- Thanks to the narrow tyre width, rounded lugs and tyre shoulders, crops and soil are optimally protected

REIFEN 380 / 95 R 38
150 A8 / 147 D, TL, AC 85 ROW CROP

Product-No.: 10926526

Technical Information:

Tyre size	380 / 95 R 38
TL / TT	TL
LI / SI	150 A8 / 147 D
Tread	AC 85 Row Crop
Manufacturer	Mitas
Recom. Rim	W12
Permissible rim	W11, W13
Width [mm]	380
Outer diameter [mm]	1680
Static radius [mm]	770
Rolling circumference [mm]	5050
Payload in kg at kph (1)	3350 / 40
Payload in kg at kph (2)	3075 / 65
Inflation pressure [bar]	2,40
Weight [Kg]	98,97
Stud height [mm]	44,0
Number of studs	24x2
Zulassung	nicht notwendig
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes

Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.