



Hints and features:

- The Alliance 533 is an industrial and construction tyre for wheel loaders and backhoes
- Its strong nylon casing offers the best conditions for off-road use on construction sites
- Its tread pattern provides good traction, braking power and high mileage when used on roads
- The tyre can also be used on municipal tractors and agricultural vehicles

REIFEN 15.5 / 80 - 24

12 PR, 157 A6 / 154 A8, TT, 533

ECE106

Product-No.: 15222273

Technical Information:

| | |
|----------------------------|-----------------|
| Tyre size | 15.5 / 80 - 24 |
| TL / TT | TT |
| LI / SI | 157 A6 / 154 A8 |
| PR | 12 |
| Tread | 533 |
| Manufacturer | Alliance |
| Recom. Rim | 12 |
| Permissible rim | 13, 14 |
| Width [mm] | 394 |
| Outer diameter [mm] | 1262 |
| Static radius [mm] | 552 |
| Rolling circumference [mm] | 3652 |
| Payload in kg at kph (1) | 4125 / 30 |
| Payload in kg at kph (2) | 3750 / 40 |
| Inflation pressure [bar] | 3,00 |
| Weight [Kg] | 68,46 |
| Stud height [mm] | 25,0 |
| Zulassung | ECE 106 |
| Direction bound | Yes |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes. Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.