Bohnenkamp Moving Professionals

CARLSTAR



Hints and features:

- Tyre for professional use on lawns, gardens and golf courses
- Durable rubber compound in conjunction with deep tread blocks
- Tread pattern optimised for stability and traction

REIFEN 31 X 13.50 - 15 8 PR, 123 A4 / 114 B, TL, MULTI TRAC C/S (345/60-15), ECE106

Product-No.: 12500701

Technical Information:

Tyre size	31 x 13.50 - 15
TL/TT	TL
LI / SI	123 A4 / 114 B
PR	8
Tread	Multi Trac C/S
Manufacturer	Carlstar
Recom. Rim	10LB
Width [mm]	340
Outer diameter [mm]	790
Static radius [mm]	356
Rolling circumference [mm]	2373
Payload in kg at kph (1)	1550 / 20
Payload in kg at kph (2)	1180 / 50
Inflation pressure [bar]	3,10
Weight [Kg]	24
Stud height [mm]	11,1
Zulassung	ECE 106

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.