





Hints and features:

- The Alliance Agri Star II is a new, modern agricultural tractor tyre with speed index "D" (up to 65 km/h) for tractors in all corresponding power ranges.
- The special Stratified Layer Technology provides very good traction and ride comfort in the field and on the road
- Stratified Layer Technology combines 2 layers of agricultural lugs so that after initial wear of the external lugs, the lower layer of lugs continue to provide traction
- Even after 40% wear, the 2nd lug layer guarantees good grip and effective traction and thus a long service life
- The wide contact area ensures low soil compaction
- The special abrasion- and punctureresistant rubber compound (Stubble Guard) protects the tyre from damage caused by grain stubble

REIFEN 360 / 70 R 24 122 D, TL, AGRI STAR II ECE106

Product-No.: 15228825

Technical Information:

Tyre size	360 / 70 R 24
TL/TT	TL
LI/SI	122 D
Tread	Agri Star II
Manufacturer	Alliance
Specification	Stubble Guard
Recom. Rim	W11
Permissible rim	W10, W12
Width [mm]	360
Outer diameter [mm]	1156
Static radius [mm]	525
Rolling circumference [mm]	3400
Payload in kg at kph (1)	1500 / 65
Inflation pressure [bar]	1,60
Weight [Kg]	59
Tyre content 75% [litre]	130,65
Stud height [mm]	42,0
Number of studs	20x2
Zulassung	ECE 106
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.