Bohnenkamp Moving Professionals



Hints and features:

- All-purpose implement tyre
- The grooved tread pattern is suitable for use on agricultural trailers, seeders and balers

REIFEN 3.50 - 8 4 PR, 51 A6, TT, S-318, 3-RIB INKL. SCHLAUCH TR13, ECE106

Product-No.: 19111071

Technical Information:

| Tyre size | 3.50 - 8 |
|----------------------------|----------|
| TL/TT | тт |
| LI / SI | 51 A6 |
| PR | 4 |
| Tread | S-318 |
| Manufacturer | Deli |
| Specification | Schlauch |
| Recom. Rim | 2.50 |
| Width [mm] | 96 |
| Outer diameter [mm] | 390 |
| Static radius [mm] | 178 |
| Rolling circumference [mm] | 1159 |
| Payload in kg at kph (1) | 195 / 30 |
| Inflation pressure [bar] | 3,00 |
| Weight [Kg] | 2,01 |
| Stud height [mm] | 6,8 |
| Zulassung | ECE 106 |
| | |

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.