



#### Hints and features:

- The Sailun SDL1 is a truck tyre for drive axles for long-haul transport
- Its tread pattern with 3 circumferential main grooves provides very good stability and ride comfort
- Narrow, horizontal grooves reduce noise emission and increase drive efficiency
- The big contact area with the road increases driving stability with a very long service life

REIFEN 295 / 80 R 22.5  
16 PR, 152 / 148 M, TL, SDL1, 3PMSF  
SAILUN (HA)

**Product-No.: 11066323**

#### Technical Information:

Tyre size	295 / 80 R 22.5
TL / TT	TL
LI / SI	152 / 148 M
PR	16
Tread	SDL1
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	8.25
Width [mm]	298
Outer diameter [mm]	1044
Static radius [mm]	486,56
Rolling circumference [mm]	3058
Payload in kg at kph (1)	3550 / 130
Loadcapacity Twin Truck	3150 / 130
Inflation pressure [bar]	8,50
Weight [Kg]	65,17
Rolling resistance	D
Wet grip	C
Rolling Noise DB	75
Rolling Noise Level	B
Stud height [mm]	17,0
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF