Bohnenkamp Moving Professionals



Hints and features:

- The Sailun SW05 is a truck winter tyre for drive axles for high traction requirements
- Its groove design provides a large contact area and thus good grip and slip resistance in wintry conditions
- The grooves and sipes consequently drain off snow and ensure safe driving on snow and ice
- The special, cold-resistant rubber compound retains its positive characteristics, even at very low temperatures

REIFEN 315 / 80 R 22.5 18 PR, 156 / 150 L (154 / 150 M), TL, SW05, 3PMSF SAILUN (HA)

Product-No.: 11066358

Technical Information:

Tyre size	315 / 80 R 22.5
TL/TT	TL
LI / SI	156 / 150 L (154 / 150 M)
PR	18
Tread	SW05
Manufacturer	Sailun
Specification	3PMSF
Recom. Rim	9.00
Permissible rim	9.75
Width [mm]	312
Outer diameter [mm]	1082
Rolling circumference [mm]	3141
Payload in kg at kph (1)	4000 / 120
Payload in kg at kph (2)	3750 / 130
Loadcapacity Twin Truck	3350 / 120
Inflation pressure [bar]	8,50
Weight [Kg]	72,34
Rolling resistance	E
Wet grip	D
Rolling Noise DB	75
Stud height [mm]	22,0
Zulassung	ECE 54, ECE 117
M+S	M+S
3PMSF	3PMSF

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.