Bohnenkamp Moving Professionals

VREDESTEIN



Hints and features:

- The Vredestein Traxion Versa is an agro-industrial tyre for telescopic handlers, backhoe loaders and harvesters
- Due to the form and structure of its lugs the tyre offers a flat and large contact area
- The curved lugs are wider in the tread centre and enable good traction
- Its reinforced sidewall in combination with a stabiliser ring grants effective protection against tyre damages

REIFEN 500 / 70 R 24 164 A8 / 164 B, TL, TRAXION VERSA ECE54

Product-No.: 14875060

Technical Information:

Tyre size	500 / 70 R 24
TL/TT	TL
LI / SI	164 A8 / 164 B
Tread	TRAXION VERSA
Manufacturer	Vredestein
Recom. Rim	DW16L
Permissible rim	DW15L, DW18L
Width [mm]	515
Outer diameter [mm]	1320
Static radius [mm]	595
Rolling circumference [mm]	4020
Payload in kg at kph (1)	5000 / 40
Payload in kg at kph (2)	5000 / 50
Inflation pressure [bar]	4,00
Weight [Kg]	122
Tyre content 75% [litre]	234
Stud height [mm]	39,0
Zulassung	ECE 54
Direction bound	Yes

All technical information in this website is based on the information provided by the manufacturers. The content is non-binding and serves solely for information purposes Bohnenkamp AG does not take liability for anything related to these details. Any liability for any immediate or indirect damages, claims for damages, consequential damages of any kind or from any legal ground, which ensued from the use of information on this website, is, provided this is lawful, utterly ruled out.